



Product Specification
WEICAI Laminating Machine for 0-40 Inch Screen for
Desktop & Laptop Displays



Semi automatic LCD polarizing stick film machine.

Device Model	CR-TM38060
Device name	LCD screen polarizing stick film machine
Device Description	Place the cleaned panel on the platform, the polarizer and panel were manually positioned and fixed by measuring the edge distance, next, the centrifugal protective film of polarizer is manually separated and placed in the material collection device, press the start button, bonding the glass substrate through the cylinder descending roller, the lead screw pushes the roller finally make polarizer accurately and quickly stick on the corresponding LCD substrate.
Equipment use	This product is suitable for the polarizing film peeling process in the surface scratch repair of various liquid crystal panels, and after that make the new polarizer stick to the glass substrate process. It is widely used in middle/large size LCD screen and display panel production, maintenance; such as LCD, TV, advertising machine.

Equipment Specifications	<ul style="list-style-type: none"> ● Suitable for LCD panel operation within 32 inches (Different sizes can be customized). ● Glass thickness: 0.3-1.1MM[Single layer glass]. ● Type of glass:TFT ● Applicable polarizer type: 2D polarizer at various angles.
Function characteristics	<ul style="list-style-type: none"> ● Unique fit structure design,can meet panel fit requirements within 65 inches . ● Hard and soft panels sticking is carried out synchronously with the tearing film (protective film). ● Long rubber wheel design, possess no deformation, anti-static, sufficient elasticity, a large contact area and other characteristics. ● The adoption of high precision parts can meet the requirements of various high-precision and large-area sticking processes. ● Sticking smooth, no bubbles, wrinkle free. 99.5% of products don't need to defoamed after bonding. ● Machine overall structure humane, safe operation, elegant appearance.
Basic parameters	<ul style="list-style-type: none"> ● Input power: AC220V 50-60HZ ● Rated power: 2KW ● Working pressure: 0.4-0.8mpa ● Applicable size: less than 32 inches (optional) ● Pressure setting: 0.01-0.8mpa Pointer adjustment ● Waste recycling device: Use synchronous motor coaxial drive,adjustable speed. ● Roller motion mode: Up-and-down type ,round trip.
Equipment material	<p>The main components are steel, electrophoresis aluminum , iron, plastic, etc.</p>
Equipment packaging	<p>Woodenboxes,non-logs (material is glued board, no fumigation is required for export).</p>
Dimensions	<p>1400X800x1300mm(L*W*H)</p>
Package Size	<p>1480X900X1430mm(L*W*H)</p>
Weight	<p>Net weight 260KG, Gross weight 280KG</p>

Address: 74/8 Dheer Pur, Nirankari Colony, Delhi- 110009

Contact Us - +91-92897 05928, +91-99995 95054, +91-99995 95057

www.antechnoarts.com